

CR22K6E-PFJ

HCFC, R-22, 60 Hz, 1 -phase, 265 V

Air Conditioning



Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance

Evap(°F)/Cond(°F)	45 / 130	45 / 100
RG(°F)/Liq(°F)	65.0 / 115.0	65.0 / 85.0
Capacity (Btu/hr)	22100	29500
Power (Watts):	2040	1670
Current (Amps):	8.00	6.60
EER (Btu/Wh):	10.80	17.70
Mass Flow (lbs/hr):	323	380
Sound Data @		
Sound Power (dBA):	72 Avg	77 Max
Vibration (mils(peak-peak)):	1.9 Avg	2.9 Max
Record Date:		

Mechanical

Number of Cylinders:	2	Displ(in ³ /Rev):	2.49
Bore Size(in):	1.66	Displ(ft ³ /hr):	302.57
Stroke(in):	0.58		
Overall Length (in):	10.23	Mounting Length (in):	7.50
Overall Width (in):	9.65	Mounting Width (in):	7.50
Overall Height (in):	13.31	Mounting Height (in):	13.69 *
Suction Size (in):		3/4 Stub	
Discharge Size (in):		1/2 Stub	
Oil Recharge (oz):		43	
Initial Oil Charge (oz):		45	
Net Weight (lbs):		62	
Internal Free Volume (in ³):			
Horse Power:			
*Overall compressor height on Copeland Brand Product's specified mounting grommets.			

Electrical

LRA-High*:	55.0	MCC (Amps):	13.8	UL File No:	
LRA-Half Winding:		RPM:		UL File Date:	28-Dec-1984
LRA Low*:		Max Operating Current:			
RLA(=MCC/1.4;use for contactor selection):		9.9			
RLA(=MCC/1.56;use for breaker & wire size selection):		8.8			
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.					
Type	Part No	Low MFD	High MFD	Volts	User Description
Start Capacitor	014-0061-16	43.0	52.0	330	LOW TORQUE
Start Capacitor	014-0061-30	130.0	156.0	330	HIGH TORQUE
Run Capacitor	014-0064-06	30.0	0.0	370	
Run Capacitor	014-0064-12	30.0	0.0	440	

Alternate Applications

Refrigerant	Freq (Hz)	Phase	Voltage	Application
R-404A HFC	50	1	220/240	High Temp
R-407C HFC	60	1	265	Air Conditioning
R-407C HFC	50	1	220/240	Air Conditioning