

# FBAM-B050-IAV-212

CFC, R-12, 60Hz, 1- Phase, 208/230 V



**Availability :**      **Obsolete**

## Mechanical

Unit Height (in):	11.9
Unit Length (in):	11.9
Unit Width (in):	13.1
Ship Weight (lbs):	65.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	1/4 F
Suction Connection Size (in)/Type:	1/2 F
Discharge Line Size(in):	0.25
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	MIN
Oil Recharge Amount (oz):	24

## Electrical

Max Fuse Size:	15
Min Circuit Ampacity:	7.6
Compressor:	RS40C2-IAV-100
Compressor LRA - Low:	
Compressor LRA - High:	24.1
Compressor LRA - Half winding:	
Compressor RLA:	5.6
UL:	Recognized
UL File #:	SA633
UL Guide Card:	LZFE2
Amps Per Motor:	0.3
Fan Motor Quantity:	1

## Air - Cooled Unit Performance

Release Date:	06-Sep-2002	Return Gas Temp. (°F):	40	
Compressor:	RS40C2-IAV-100    x    1	Subcooling (°F):	5	
Performance No:	5502	Air Flow Rate (CFM)	330	
<b>90°F Ambient Air Temperature</b>				
<b><u>Evap Temp</u></b>	<b><u>Unit Capacity</u></b>	<b><u>Cond. Temp.</u></b>	<b><u>Temp. Diff.</u></b>	<b><u>EER</u></b>
<b><u>(°F)</u></b>	<b><u>(Btu/hr)</u></b>	<b><u>(°F)</u></b>	<b><u>(°F)</u></b>	<b><u>(Btu/Wh):</u></b>
20	4,350	117.0	27.0	4.8