

KAGA-015A-TAD

HCFC, R-22, 60Hz, 3- Phase, 460 V
High Temp



Production Status: This model is obsolete and is no longer in production for both OEM and service replacement. Please contact Customer Service about possible replacement models.

Performance

Evap(°F)/Cond(°F)	45 / 130	20 / 120
RG(°F)/Liq(°F)	65.0 / 130.0	65.0 / 120.0
Capacity (Btu/hr)	15800	9530
Power (Watts):	1590	1250
Current (Amps):	2.60	2.20
EER (Btu/Wh):	9.90	7.60
Mass Flow (lbs/hr):	249	139
Sound Power (dBA):		
Vibration (mils(peak-peak)):		4.76 Max
Record Date:	2008-11-03	

Mechanical

Number of Cylinders:	2	Displ(in ³ /Rev):	3.05
Bore Size(in):	1.44	Displ(ft ³ /hr):	185.13
Stroke(in):	0.94		
Overall Length (in):	14.38	Mounting Length (in):	8.19
Overall Width (in):	9.50	Mounting Width (in):	6.38
Overall Height (in):	10.44	Mounting Height (in):	11.19 *
Suction Size (in):		7/8 Sweat	
Discharge Size (in):		1/2 Flare	
Oil Recharge (oz):		20	
Initial Oil Charge (oz):		22	
Net Weight (lbs):		96	
Internal Free Volume (in ³):			
Horse Power:			
*Overall compressor height on Copeland Brand Product's specified mounting grommets.			

Electrical

LRA-High*:	18.2	MCC (Amps):	3.5	UL File No:	SA-2337
LRA-Half Winding:		RPM:	3500	UL File Date:	23-Jul-1984
LRA Low*:		Max Operating Current:			
RLA(=MCC/1.4;use for contactor selection):		2.5			
RLA(=MCC/1.56;use for breaker & wire size selection):		2.2			
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.					

Alternate Applications

Refrigerant	Freq (Hz)	Phase	Voltage	Application
R-22 HCFC	50	3	380/400	High Temp