

KANB-005E-CAV

CFC, R-12, 60Hz, 1- Phase, 208/230 V

High Temp



Production Status: This compressor and/or application of this compressor is not available to U.S. OEM customers. A field replacement is currently available through a U.S. Emerson Climate Technologies Wholesaler. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance

Evap(°F)/Cond(°F)	45 / 130	20 / 120
RG(°F)/Liq(°F)	65.0 / 130.0	65.0 / 120.0
Capacity (Btu/hr)	5860	3400
Power (Watts):	580	460
Current (Amps):	2.70	2.40
EER (Btu/Wh):	10.10	7.40
Mass Flow (lbs/hr):	116	63
Sound Power (dBA):		
Vibration (mils(peak-peak)):		4.76 Max
Record Date:	2006-10-16	

Mechanical

Number of Cylinders:	2	Displ(in ³ /Rev):	1.86
Bore Size(in):	1.38	Displ(ft ³ /hr):	112.78
Stroke(in):	0.62		
Overall Length (in):	14.38	Mounting Length (in):	8.19
Overall Width (in):	9.50	Mounting Width (in):	6.38
Overall Height (in):	10.44	Mounting Height (in):	11.19 *
Suction Size (in):		1/2 Flare	
Discharge Size (in):		3/8 Flare	
Oil Recharge (oz):		20	
Initial Oil Charge (oz):		22	
Net Weight (lbs):		83	
Internal Free Volume (in ³):			
Horse Power:			
*Overall compressor height on Copeland Brand Product's specified mounting grommets.			

Electrical

LRA-High*:	24.0	MCC (Amps):	5.1	UL File No:	
LRA-Half Winding:		RPM:	3500	UL File Date:	23-Jul-1984
LRA Low*:		Max Operating Current:			
RLA(=MCC/1.4;use for contactor selection):		3.6			
RLA(=MCC/1.56;use for breaker & wire size selection):		3.3			
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.					
Type	Part No	Low MFD	High MFD	Volts	User Description
Start Capacitor	014-0061-29	108.0	130.0	330	
Run Capacitor	014-0064-00	10.0	0.0	370	

Alternate Applications

Refrigerant	Freq (Hz)	Phase	Voltage	Application
R-12 CFC	50	1	200/220	
R-12 CFC	50	1	200/220	Medium Temperature
R-22 HCFC	50	1	200/220	
R-502 CFC	50	1	200/220	Low Temperature
R-404A HFC	50	1	200/220	Low Temperature
R-507 HFC	50	1	200/220	Low Temperature
R-12 CFC	60	1	208/230	Medium Temperature
R-22 HCFC	60	1	208/230	Low Temperature
R-502 CFC	60	1	208/230	Low Temperature

Alternate Applications

<u>Refrigerant</u>	<u>Freq (Hz)</u>	<u>Phase</u>	<u>Voltage</u>	<u>Application</u>
R-404A HFC	60	1	208/230	Low Temperature
R-507 HFC	60	1	208/230	Low Temperature