

H46C1166

24/120/240 Vac Wall mounted Premier White® Dehumidistat



Overview

Provide automatic control of a humidifier or dehumidifier for dehumidification in air conditioning systems.

Features

- Positive ON-OFF settings permit manual operation of controlled equipment.
- Impact-resistant, molded plastic cover mounts on wall.
- Fully enclosed, dust free, SPST, snap-acting switch.
- Sensing element of thin, moisture sensitive nylon ribbon provides reliable operation even when ambient temperature conditions change.

Product Specifications

Description	Wall mounted Dehumidistat
Application	Dehumidification
Type	Humidity Control
Voltage	120 Vac
Voltage	240 Vac
Voltage	24 Vac
Electrical Ratings (120 Vac, Full Load)	7.5A
Electrical Ratings (120 Vac, Locked Rotor)	30.0A
Electrical Ratings (120 Vac, Resistive)	12.0A
Electrical Ratings (240 Vac, Full Load)	3.8A
Electrical Ratings (240 Vac, Locked Rotor)	15.0A
Electrical Ratings (240 Vac, Resistive)	6.0A
Color	Premier White®
Mounting	Wall mount
Differential	4% to 6% RH
Temperature Range (F)	50 F to 125 F
Temperature Range (C)	10 C to 52 C
Operating Humidity Range (% RH)	20 to 80% RH
Dimensions (in.)	4 11/16 in. high x 2 15/16 in. wide x 2 1/8 in. deep

Dimensions (mm)

119 mm high x 75 mm wide x 54 mm deep

Tradeline Value

Tradeline