

Split Phase Belted Fan & Blower

Open Dripproof, NEMA[®]† 56 Frame, Single & Two Speed




APPLICATIONS:

Designed to meet manufacturer's requirements for belted fans and blowers.

FEATURES:

- Resilient Base
- Class B Insulation Unless Otherwise Noted
- With Threaded Conduit Hole
- Reversible Rotation
- Automatic Reset Thermal Overload Protector
- **Discount Symbol: DS-3HAC**



Single Speed, NEMA 56[†] Frame

HP	RPM	Volts	Catalog Number	List	Bearings	NEMA Frame	Amps	Shaft N	Shaft U	Protector	Total C	SF	Ship Wgt.	Notes
1/3	1725	115	4253	\$280	Slv	56Z	5.8	1.5	.500	Auto	8.9	1.35	18	77, A
	1725	115	2766	\$344	Slv	56	5.7	1.9	.625	Auto	10.3	1.35	19	A
1/2	1725	115/230	4114	\$368	Slv	56	8.0/4.0	1.9	.625	Auto	9.8	1.25	22	
3/4	1725	115/230	4115	\$387	Slv	56	11.2/5.6	1.9	.625	Auto	9.8	1.25	24	

Two Speed, NEMA[†] 56 Frame

HP	RPM	Volts	Catalog Number	List	Bearings	NEMA Frame	Amps	Shaft N	Shaft U	Protector	Total C	SF	Ship Wgt.	Notes
1/4	1725/1140	115	5792C	\$289	Slv	56Z	5.1	1.5	.500	Auto	9.9	1.00	18	81
1/3	1725/1140	115	5793C	\$309	Slv	56Z	6.4	1.5	.500	Auto	10.4	1.00	19	81
	1725/1140	115	6470	\$292	Ball	56Z	6.9	1.6	.500	Auto	8.9	1.00	20	23
1/2	1725/1140	115	5794C	\$400	Slv	56Z	8.7	1.5	.500	Auto	10.4	1.00	25	81
	1725/1140	115	4293	\$412	Slv	56	9.2	1.9	.625	Auto	10.8	1.25	26	A
	1725/1140	230	4293H	\$407	Slv	56	4.6	1.9	.625	Auto	10.8	1.25	26	A
3/4	1725/1140	115	1832	\$481	Slv	56	11.4	1.9	.625	Auto	11.3	1.00	23	
	1725/1140	115	5795C	\$482	Slv	56	11.5	1.9	.625	Auto	11.3	1.00	23	81

Note 23 Manual Reset Thermal Overload Protector
 Note 77 With Shaft Adapter For 5/8" Shaft

Note 81 Canadian Standard — May Be Used With Single Pole Single Throw Switch, Not Stocked For US Distribution
 Note A Class A Insulation

† All marks shown within this document are properties of their respective owners



DRIVES
 BRAKE MOTORS
 GENERAL PURPOSE SINGLE PHASE
 HVAC
 WASHDOWN
 AGRICULTURE
 COMMERCIAL PUMP MOTORS
 CLOSE COUPLED PUMP MOTORS
 FIRE PUMP MOTORS
 POOL & SPA MOTORS
 RESIDENTIAL WATER PUMP
 ELEVATOR AND GATE & DOOR